

TF1 OMEGA FILTER FLUSHING ADAPTER

The Fernox TF1 Omega Filter Flushing Adapter quickly and easily connects a Fernox Powerflow Flushing Machine to the heating system via a Fernox TF1 Omega Filter. It is fitted by simply replacing the filter body with the adapter.

Benefits of using a Fernox TF1 Omega Filter Flushing Adapter

- Fast, easy flushing with connection via the Fernox TF1 Omega Filter
- Enables the full flow rate to optimise cleaning efficiency
- Allows the primary side of the secondary heat exchanger on combination boiler to be cleaned by simply turning on the domestic hot water tap to engage the boiler diverter valve
- Fernox TF1 Omega Filter Flushing Adapter is rated to 85°C

Maintenance

When used appropriately, the Fernox TF1 Omega Filter Flushing Adapter is maintenance free.

Instructions

1. Drain the central heating system water.
2. Replace the TF1 Omega Filter body with the TF1 Omega Filter Flushing Adapter.
3. Connect the Fernox Powerflow Flushing Machine to the TF1 Omega Filter Flushing Adapter. Use 3/4" BSP female nut liner and seals, as provided with the Fernox Powerflow Flushing Machine.

Packaging, Handling and Storage

Individually packaged with instructions included. No special storage requirements.



Tel: +44 (0) 330 100 7750 Email: sales@fernox.com

Product code: 62289